



# Material Safety Data Sheet

## PRODUCT IDENTIFICATION

**APT-II CERAMIC ENHANCER**

### APT-II Products Co.

#### Hazard Rating

Toxicity	0
Fire	0
Reactivity	0
Special	-

#### Scale

4=EXTREME
3=HIGH
2=MODERATE
1=SLIGHT
0=INSIGNIFICANT

## COMPONENT INFORMATION

### No.

- 1 Acrylic copolymer .....
- 2 Water.....
- 3 Residual monomers.....

### CAS REG NO.

Not Hazardous  
7732-18-5  
Not Required

# EMERGENCY RESPONSE INFORMATION

## FIRST AID PROCEDURES

- |                     |   |
|---------------------|---|
| <u>Inhalation</u>   | Move subject to fresh air.  |
| <u>Eye Contact</u>  | Flush eyes with a large amount of water for at least 15 minutes. Consult a physician if irritation persists.                |
| <u>Skin Contact</u> | Wash affected skin areas thoroughly with soap and water.  |
| <u>Ingestion</u>    | If swallowed, give 2 glasses of water to drink. Consult a physician. Never give anything by mouth to an unconscious person. |

## FIRE FIGHTING INFORMATION

- |                                      |  |
|--------------------------------------|--|
| <u>Unusual Hazards</u>               | Material can splatter above 100C/212F. Polymer film can burn.  |
| <u>Extinguishing Agents</u>          | Use extinguishing media appropriate for surrounding fire.  |
| <u>Personal Protective Equipment</u> | As in any fire, wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear. |

---

# HAZARD INFORMATION

---

## HEALTH EFFECTS FROM OVEREXPOSURE

---

### Primary Routes of Exposure

Skin Contact  
Eye Contact

### Inhalation

Inhalation of high solvent vapor or mist concentrations can cause the following: headache, nausea, and irritation of nose, throat, and lungs

### Eye Contact

Material can cause the following: slight irritation

### Skin Contact

Prolonged or repeated skin contact can cause the following:  
Slight skin irritation

### Ingestion

Material is possibly harmful if swallowed.

---

## FIRE AND EXPLOSIVE PROPERTIES

---

Flash Point . . . . .	Noncombustible
Auto-ignition Temperature . . . . .	Not Applicable
Lower Explosive limit . . . . .	Not Applicable
Upper Explosive limit . . . . .	Not Applicable

---

## REACTIVITY INFORMATION

---

### Instability

This material is considered stable. However, avoid temperatures above 177C/350F, the onset of polymer decomposition. Thermal decomposition is dependent on time and temperature.

### Hazardous Decomposition Products

There are no known hazardous decomposition products for this material.

### Hazardous Polymerization

Product will not undergo polymerization.

---

---

# ACCIDENT PREVENTION INFORMATION

---

## COMPONENT EXPOSURE INFORMATION

---

### Component Information

No.		CAS REG NO.
1	Acrylic copolymer .....	Not Hazardous
2	Water.....	7732-18-5
3	Residual monomers.....	Not Required

---

### Exposure Limit Information

Component		APT-II PRODUCTS		OSHA		ACGIH	
No.	Units	TWA	STEL	TWA	STEL	TLV	STEL
1		None	None	None	None	None	None
2		None	None	None	None	None	None
3		a	a	a	a	a	a

a Not Required

---

## STORAGE AND HANDLING INFORMATION

---

Storage Conditions                      The minimum recommended storage temperature for this material is 1 C/34F.  
The maximum recommended storage temperature for this material is 49C/120F.

---

# SUPPLEMENTAL INFORMATION

---

### TYPICAL PHYSICAL PROPERTIES

Appearance .....	Milky
Color .....	White
State .....	Fluid
PH .....	6.0-7.0
Viscosity .....	< 100 CPS @20°C/68°F
Specific Gravity (Water = 1).....	1.06 Approximate
Vapor Density (Air = 1) .....	0.62 Water
Vapor Pressure .....	17 mm Hg Water
Melting Point.....	0°C/32°F Water
Boiling Point .....	100°C/212°F Water
Solubility in Water .....	Dilutable
Evaporation Rate (BAC - 1) .....	< 1 Water

---

---

## TOXICITY INFORMATION

---

### Acute Data

The information shown in the HEALTH EFFECTS FROM OVEREXPOSURE Section is based on the toxicity profiles for a number of acrylic emulsions that are compositionally similar to this product. Typical data are:

Oral LD50 - rat: >5000 mg/kg  
Dermal LD50 - rabbit: >5000 mg/kg  
Eye Irritation - rabbit slight irritation  
Skin Irritation - rabbit no irritation

---

## WASTE DISPOSAL

---

### Procedure

For disposal, incinerate this material at a facility that compiles with local, state, and federal regulations.

---

## REGULATORY INFORMATION

---

### WORKPLACE CLASSIFICATIONS

This product is considered non-hazardous under the OSHA Hazard Communication Standard (29CFR 1910.1200).

This product is not a “controlled product” under the Canadian Workplace Hazardous Materials Information System (WHMIS).

---

### TRANSPORTATION CLASSIFICATIONS

US DOT                      Hazard Class . . . . . NONREGULATED

---

### EMERGENCY PLANNING & COMMUNITY RIGHT-TO-KNOW (SARA TITLE 3)

#### Section 311/312 Categorizations (40CFR 370)

This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.

#### Section 313 Information (40CFR 372)

This product does not contain a chemical which is listed in Section 313 above de minimis concentrations.

---

---

CERCLA INFORMATION (40cfr 302.4)

Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

---

RCRA INFORMATION

When a decision is made to discard this material as supplied, it does not meet RCRA's characteristic definition of ignitability, corrosivity, or reactivity, and is not listed in 40 CFR 261.33.

---

CHEMICAL CONTROL LAW STATUS

All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

---

STATE RIGHT-TO-KNOW LAWS

Any material listed as "Not Hazardous" in the CAS REG NO column of the COMPONENT INFORMATION Section of this MSDS is trade secret under the provisions of the *Texas Worker an Community Right-to-Know Act*.

---

ABBREVIATIONS:

ACGIH = American Conference of Governmental Industrial Hygienists  
OSHA = Occupational Safety and Health Administration  
TLV = Threshold Limit Value  
PEL = Permissible Exposure Limit  
TWA = Time weighted Average  
STEL = Short-Term Exposure Limit  
BAc = Butyl acetate  
Bar denotes a revision from previous MSDA in this area.

---

The information contained herein relates only to the specific material identified. APT-II Products Co. believes that such information is accurate and reliable as of the date of this material safety data sheet, but no representation, guarantee or warranty, express or implied, is made as to the accuracy, reliability, or completeness of the information. APT-II Products Co. urges persons receiving this information to make their own determination as to the information's suitability and completeness for their particular application.

---